# HKOKI

#### **POWER TOOL INNOVATIONS & REDEMPTION DEALS** AUGUST - NOVEMBER 2024

# UNLEASH MORE POYAER

HÍKOKI TPWR




### TABLESS CELL TECHNOLOGY

HiKOKI continues to lead the way in MULTI VOLT battery technology with a powerful new tabless 21700 lithium-ion battery cell.

The HiKOKI T-PWR Tabless Battery (BSL3640MVT) has been built with less internal resistance allowing for more power to flow from the tabless battery to the power tool increasing both the overload capacity and tool speed.

This diagram shows the difference between HiKOKI's new T-PWR tabless cell vs a conventional cell. The power of the conventional cell gets bottlenecked at a single positive and negative tab while the tabless cell delivers free-flowing power with low resistance.





T-PWR 21700 TABLESS CELL CONVENTIONAL 21700 CELL

Cooling System Interface

#### **POWERFUL MULTI VOLT** TABLESS TECHNOLOGY

Industry leading battery technology packed into a single battery pack.





**RECHARGE CYCLES** 

3-Way Protection Circuitry

**LED Status Indicator** 

10x 21700 Tabless Cells

Drain Outlets

18V/36V Auto Switching

Battery Management System with Upgradable Firmware

Water Resistant Cell Cover

Thermoplastic **Elastomer Housing** 

Impact Resistant Housing

**Cool Chassis Maximises Airflow** 

# HIKOKI T. PWR HÍKOKI TPWR

# THE MULTI VOLT ADVANTAGE

HiKOKI MULTI VOLT High Output Batteries redefine tool performance and power. Supercharge your work with HiKOKI's new high output cordless system powering over 190+ tools across two voltages.



### UNLEASH MORE TOOL POWER

HiKOKI MULTI VOLT Tabless Battery delivers more power to high energy power tools. T–PWR delivers G3613DVF more max output power, faster grinding and cutting speeds resulting in more productivity.

Example: G3613DVF cutting performance (BSL36B18X vs BSL3640MVT)



**30%** MORE CONCRETE WITH HIKOKI T-PWR BATTERY

CUI

power when using G3613DVF with BSL3640MVT

BSL36B18X

27% more output

MORE OUTPUT

POWER

UNLEASH FASTER CHARGING

#### NEW UC36YSL2 12A MAX FAST CHARGER

HiKOKI unleash the new 12Amp Max Fast Charger delivering unparalleled lightening quick charging times with extra safety benefits. UC36YSL2 features the latest in cutting-edge cooling systems, 3-way protection including overcharging and overheating technology. The UC36YSL2 is also compatible with generators and features a highly visible charge status light to easily identify the charging status wherever you are on the worksite.







FAST CHARGER

CHARGING TIMES:



coo







# **New High Performance Power Tools**

#### 18V 450g Grease Gun Kit

AL18DA(GRZ)

- Variable flow dial with 10 pre-set discharge pressure settings
- 690 bar max. discharge pressure
- 3-way filling system
- Lock-on trigger

charger, case.

■ Two-mode operation (High/Low)

Supplied with 1x1080W battery,

Barrel Capacity	450g	And the second
Flow Rate	High: 297mL / Low: 115mL	
Max. Pressure	69/41MPa	
Speed Modes	2 Modes	
Flow Settings	10 Flow Settings	
Hose Length	1200mm	C B B
Weight	4.3kg (BSL36B18X)	
Voltage	18V	Scan for tool specs.

#### **18V** Brushless Air Duster BARE TOOL

RA18DA(G4Z)

- Variable speed control
- Lightweight and compact design
- Built-in LED light
- Tool-less nozzle changing
- Blowing, inflating and deflating nozzle

Supplied without batteries and charger. Includes Dust, Suction, Inflating & deflating nozzles.

Max. Airflow	0.7m3/min
Air Velocity	High: 122m/s Low: 100m/s
Max. Pressure	18kPa / 2.61PSI
No Load Speed	89,000/min
Switch Style	Trigger
Motor Type	Brushless
Weight	1.2kg (BSL36A18X)
Voltage	18V



#### 18V 160psi Dual Pump Inflator **BARE TOOL**

UP18DA(W4Z)

- High pressure mode for tyre inflation
- High volume mode for air beds
- Auto stop function
- Large LED status display
- Power via Battery or 12V DC adaptor Supplied without batteries and charger. Includes 12V DC adaptor

Max. Pressure	160PSI
Filling Capacity (HP)*	16L/min at 130kPa
Filling Capacity (HV)*	430L/min
Hose Length (HP)	1200mm
Hose Length (HV)	490mm
LED Light	Yes
Weight	3.8kg (BSL36A18X)
Voltage	18V





Scan for tool specs.

#### 18V 450g Grease Gun BARE TOOL

AL18DA(G4Z)

- Variable flow dial with 10 pre-set discharge pressure settings
- 690 bar max. discharge pressure
- 3-way filling system
- Lock-on trigger
- Two-mode operation (High/Low)
- Supplied without batteries and charger.



Barrel Capacity	450g
Flow Rate	High: 297mL / Low: 115mL
Max. Pressure	69/41MPa
Speed Modes	2 Modes
Flow Settings	10 Flow Settings
Hose Length	1200mm
Weight	4.3kg (BSL36B18X)
Voltage	18V

Scan for tool specs

#### **36V** Brushless SDS-MAX Demolition Hammer BARE TOOL

H3641DA(H2Z)

- Equivalent performance to H41MB2 AC model
- Compact and lightweight model
- Low vibration Handle (LVH)
- Tool angle adjustment system
- Variable speed control

Supplied without batteries and charger. Includes side handle, bullpoint attachment

Bit Shank	SDS-MAX
Impact Rate (High)	2,880/min
Impact Rate (Low)	1,500/min
Full Load Vibration	9.7/m/s <sup>2</sup>
Anti-Vibration System	LVH
Motor Type	Brushless
Weight	5.8kg (BSL36A18X)
Voltage	36V



18V HEPA 13 Wet & Dry Vac

#### **BARE TOOL**

RP18DA(W4Z)

- Compact, lightweight and portable
- Two suction modes (Eco / Boost Mode)
- Press clean button
- Dry and wet vacuuming
- HEPA 13 Filter

Supplied without batteries and charger. Includes hose, tubes, crevice & wide nozzle.

Filter Type	HEPA 13
Suction Work Rate	Boost: 35W / Eco: 80W
Runtime (BSL36B18X)	up to 44.5mins*
Max. Airflow	2.1m³/min
Max. Vac Pressure	12kPa
Protection Class	IPX4
Weight	5.1kg (BSL36B18X)
Voltage	18V





Scan for tool specs








# **Unleash High Performance Grinding**

Get more grinding power and performance with HiKOKI T/PWR

#### **18V** Brushless 125mm Angle Grinder

BARE TOOL

- G1813DA(G4Z)
- Anti-kickback, Restart and Overload protection
- Powerful grinding with 950W max output\*
- Anti-vibration handle
- Slide Switch for easy on/off





Supplied without batteries and charger. Includes side handle, guard, grinding wheel.

Wheel Diameter	125mm
Spindle Thread	M14 x 2
Hole Diameter	22.24mm
No Load Speed	8,000/min
Swith Style	Slide Switch
Motor Type	Brushless
Weight	2.4kg (BSL36A18X)
Voltage	18V



Scan for tool specs.

#### **36V** Brushless 125mm Angle Grinder BARE TOOL

G3613DVE(G4Z)

- Powerful grinding with 1900W max output\*
- Anti-kickback, Restart, Brake and Overload protection
- Self Protection Mode
- Variable Speed and AUTO mode



Supplied without batteries and charger. Includes side handle, guard, grinding wheel.

-		
Wheel Diameter	125mm	
Spindle Thread	M14 x 2	
Hole Diameter	22.24mm	_
No Load Speed	3,200 – 10,000/min	
Swith Style	Slide Switch	22
Motor Type	Brushless	22
Weight	2.8kg (BSL36A18X)	
Voltage	36V	Scan f

#### **36V** Brushless 180mm Angle Grinder BARE TOOL

#### G3618DA(G4Z)

- Variable speed and AUTO mode
- Anti-kickback, Restart, Brake and Overload protection
- Low vibration handle
- Lock-on/off trigger

Supplied without batteries and charger. Includes side handle, guard, grinding wheel.

Wheel Diameter	180mm
Spindle Thread	M14 x 2
Hole Diameter	22.24mm
No Load Speed	3,200 – 5,300/min
Swith Style	Slide Switch
Motor Type	Brushless
Weight	4.7kg (BSL36A18X)
Voltage	36V



Scan for tool specs.

#### **18V** Brushless 125mm Angle Grinder BARE TOOL

G1813DF(G4Z)

- Anti-kickback, Restart, Brake and Overload protection
- Powerful grinding with 950W max output\*
- Anti-vibration handle
- Paddle Switch for added safety
- $\blacksquare$  Variable Speed with AUTO mode

#### Supplied without batteries and charger. Includes side handle, guard, grinding wheel.

Wheel Diameter	125mm
Spindle Thread	M14 x 2
Hole Diameter	22.24mm
No Load Speed	8,000/min
Swith Style	Paddle Switch
Motor Type	Brushless
Weight	2.4kg (BSL36A18X)
Voltage	18V

Scan for tool specs

### **36V** Brushless 125mm Angle Grinder BARE TOOL

G3613DVF(G4Z)

- Powerful grinding with 1900W max output\*
- Anti-kickback, Restart, Brake and Overload protection
- Self Protection Mode
- Variable Speed and AUTO mode
- Safety deadman switch

Supplied without batteries and charger.

Includes side handle, guard, grinding wheel.

Wheel Diameter	125mm
Spindle Thread	M14 x 2
Hole Diameter	22.24mm
No Load Speed	3,200 – 10,000/min
Swith Style	Paddle Switch
Motor Type	Brushless
Weight	2.8kg (BSL36A18X)
Voltage	36V



Scan for tool specs

### **36V** Brushless 230mm Angle Grinder BARE TOOL

G3623DA(G4Z)

- Variable speed function and AUTO mode
- Anti-kickback, Restart, Brake and Overload protection
- Low vibration handle
- Lock-on/off trigger

Supplied without batteries and charger. Includes side handle, guard, grinding wheel.

Wheel Diameter	230mm
Spindle Thread	M14 x 2
Hole Diameter	22.24mm
No Load Speed	3,200 – 5,300/min
Swith Style	Slide Switch
Motor Type	Brushless
Weight	4.9kg (BSL36A18X)
Voltage	36V





Ηίκοκι

\*Max Power using HiKOKI T–PWR

### Torque Boost Technology





New Torque Boost Technology combines precision, power and speed for the perfect smooth cut every time even under heavy load.

Torque Boost Technology combined with the Smart Auto Switch Mode automatically adjusts no-load speed and torque depending on the load and application. Auto Switch Mode automatically adjusts no load speed between 6,000rpm (High Speed Cutting) and 4,500rpm (High Torque) achieving high speed cutting and high efficiency improving productivity.



0 Ratio %

#### **36V** Brushless 185mm Circular Saw Kit

#### C3607DB(GVZ)

#### NEW Torque Boost Technology

- Smart AUTO switch function
- 33% increase in no-load speed\*
- 185mm Blade max cut 62mm at 90°
- 2 mode speed control

Supplied with 1x 1440W Multi Volt Battery, Rapid Charger, TCT Blade, Rafter Hook, Case and Wrench

Blade Diameter	185mm	
Max. Cut 90°	62mm	
Max. Cut 45°	47.5mm	
Modes	Auto Switch / High Torque	
No Load Speed	4.500/min / 6,000/min	
Motor Type	Brushless (Torque Boost)	
Weight	4.6kg (BSL36B18X)	
Voltage	36V	





Scan for tool specs

100





**36V** Brushless 305mm Slide

**Compound Mitre Saw Kit** 

■ Front bevel angle: Left / Right 45°

200

Compatible with AC Power Adaptor\*

Supplied with 1080W Multi Volt Battery, Rapid Charger, TCT Blade and Wrench

Blade Diameter	305mm «	
Mitre Angle	L: 45° / R: 57°	
Bevel Angle	L: 5° / R: 45°	
XACT Cut LED	Yes	
No Load Speed	3,200/min / 4,000/min	
Motor Type	Brushless (Torque Boost)	
Weight	26.2kg (BSL36A18X)	
Voltage	36V	



**CUTTING** 

Cutting speed is approximately 2 times faster than C3607DA when cutting SPF2x10 timber in Auto Switch mode.

FASTER SPEED

Fast Cutting Speed



Scan for tool specs

# **High Powered Saws & Accessories**

Get more cutting power and performance with **HiKOKI** T/PWR

#### **36V** Brushless 255mm Slide Compound Mitre Saw BARE TOOL

C3610DRA(H4Z)

- Compact slide system
- Laser Marker Guide
- Powerful 36V brushless motor
- Front bevel angle: Left / Right 48°
- Compatible with AC Power Adaptor\*

Supplied without batteries and charger. Includes side handle, guard, and blade.

nm	
60°	

Blade Dia.	255mm
Mitre Angle	L: 55°/R: 60°
Bevel Angle	L: 48°/R: 48°
Laser Marker	Yes
No Load Speed	4,000/min
Motor Type	Brushless
Weight	20.6kg (BSL36A18X)
Voltage	36V
voltage	367



Scan for tool spece

#### **36V** Brushless 185mm Rear Handle **Circular Saw BARE TOOL** C3607DWA(G4Z)

- 185mm Blade max cut 62mm at 90
- Bevel Capacity 53°
- with stops 22.5°, 45°, 53 Durable and lightweight base
- Electronic brake and soft start

Supplied without batteries and charger. Includes side handle, guard, and blade.

Blade Dia.	185mm	
Max Cut 90°	63mm	
Max Cut 45°	45mm	
Max Cut 53°	38mm	出版
No Load Speed	5,100/min	
Motor Type	Brushless	1
Weight	4.7kg (BSL36A18X)	<u> <u> </u></u>
Voltage	36V	Scan for too

#### **36V** Brushless 165mm Circular Saw **BARE TOOL**

C3606DB(G4Z)

- 165mm Blade max cut 66mm at 90
- Super compact and lightweight
- Bevel capacity max cut 45mm at 45
- Quick and easy blade change
- Silent mode and soft start

Supplied without batteries and charger. Includes dust exhaust, blade, wrench

Max Cut 90° 66mm   Max Cut 45° 45mm   Handle Position D-Handle	Diada Dai	
Max Cut 45°     45mm       Handle Position     D-Handle	Blade Dal.	165mm
Handle Position     D-Handle	Max Cut 90°	66mm
	Max Cut 45°	45mm
No Load Speed 2.000/min / 5.600/min	Handle Position	D-Handle
	No Load Speed	2,000/min / 5,600/min
Motor Type Brushless	Motor Type	Brushless
Weight 3.7kg (BSL36A18X)	Weight	3.7kg (BSL36A18X)
Voltage 36V	Voltage	36V





Scan for tool specs

#### **Universal** Mitre Saw Stands KSU100 / KSU401



KSU401

KSUIOO

	100 101	
1000mm	Length	1680mm
250kg	Max. Weight	250kg
16kg	Stand Weight	25kg
1 Pair	Machine Assembly	1 Pair
Yes	Universal	Yes
Lockable	Foldable Legs	Lockable
	250kg 16kg 1 Pair Yes	1000mmLength250kgMax. Weight16kgStand Weight1 PairMachine AssemblyYesUniversal

#### **36V** Brushless 165mm Plunge Saw **BARE TOOL**

C3606DPA(G5Z)

- Accurate precision cutting when fitted to rail\*
- Variable speed function
- Double guide for superior precision
- Fast brake function
- Compatible with HiKOKI rail system\*

Supplied without batteries and charger. Includes Case, blade, dust port, dust bag, hex wrench.

Blade Dai.	165mm
Max Cut 90°	66mm
Max Cut 45°	43mm
Bevel Angle	-1 to 46°
No Load Speed	2,500/min / 5,200/min
Motor Type	Brushless
Weight	5.1kg (BSL36A18X)
Voltage	36V
Voltage	36V



Scan for tool specs

#### 18V Brushless 135mm Metal Cutting Saw BARE TOOL

CD1805DB(G4Z)

- 135mm Metal TCT blade accepts up to 150mm blades
- Max cutting depth of 51.5mm
- Overload and anti-kickback protection
- Power mode and silent mode

Supplied without batteries and charger. Includes 135mm blade, chip shroud, wrench

Blade Dai.	135mm
Max Cutting Depth	51.5mm
Base Material	Stainless Steel
Handle Position	D-Handle
No Load Speed	2,200/min / 4,200/min
Motor Type	Brushless
Weight	3.1kg (BSL36A18X)
Voltage	18V







# **High Powered Saws & Accessories**

BARE TOOL C3610DRJ(G4Z) Large table size (7	inion adjustment system ctric brake rip fence AC Power Adaptor*	ble Saw	<b>36V AC Powe</b> ET36A(HOZ) Powers HiKOKI 36V Pow 6m long power lead Pivoting cord position Lamp indicator Overload/Overheat protection		
Includes TCT blade, pu	sh stick, wrench		Power Output	2000)W/ /ZGV/	-
Blade Dia.	255mm		Fan-cooled	2000W (36V)	
Cutting Depth	90°: 79mm / 45°: 57mm			Yes	
No Load Speed	5,000/min		Runtime		ത്രംജ്ജ്
Rip Fench Length	R: 889mm / L: 445mm		Operating Temperature	-10°C - 40°C	
Table Size	730 x 560mm		Cord Length	6m	2015 (1997) 2015 (1997)
Motor Type	Brushless		Indicator Status Lights	Yes	
Weight	29.5kg (BSL36A18X)	国家的委托	Pivoting Cord Range	90° - 180°	
Voltage	36V	Scan for tool specs.	Weight	0.8kg (adaptor)	Scan for tool specs.
MULTI VOI Starter Kit UC18YSL3(HJZ)		narger	MULTI VOLT BSL3640MVT / BSL36B1 Up to 1500 recharge c Smart battery indicate	8X ycles*	ut Batteries

- 1080W MULTI VOLT Battery
- Powers both 18V & 36V Tools
- 32min Rapid Charging
- Fan-cooled charging

Battery Type Charging Time

Fan-cooled Charging

**Recharge Cycles** 

LED Status Light

Protection

USB Port Out

**Generator Safe** 


Bright LED status light



Scan for tool specs.

■ Shock resistant housing





BSL3640MVI	
Max. Power Output	2160W
Voltage	18V/36V
Amp Hours (18V/36V)	8.0Ah / 4.0Ah
Battery Indicator	4 LED Levels
Cell Type	21700
Heat Protection	Yes
<b>Overload Protection</b>	Yes

C'S APPLY. VIA REDEM



BSL36B18X

Max. Power Output	1440W	
Voltage	18V/36V	
Amp Hours (18V/36V)	rs (18V/36V) 8.0Ah / 4.0Ah	
Battery Indicator	4 LED Levels	
Cell Type	21700	
Heat Protection	Yes	
Overload Protection	Yes	

### 254mm AC Worksite Tablesaw with Stand

- CIORJ
- Large table size (730 x 560mm)
- Accurate rack & pinion adjustment system
- Soft-start and electric brake
- Large adjustable rip fence
- Folding stand with wheels
- Large extension support table to cut long material

MULTI VOLT (BSL36A18X)

Over Heat/Over Charge

32 mins.

up to 1500\*

Yes

Yes

Yes

Yes

Supplied Folding Stand, TCT blade, push stick, wrench

Blade Dia.	254mm
Cutting Depth	90°:79mm/45°:57mm
No Load Speed	4,500/min
Rip Fench Length	R: 889mm / L: 445mm
Table Size	730 x 560mm
Blade Bore	30mm
Weight	44kg
Voltage	230V



Scan for tool specs



## **Rotary & Demolition Hammers**

#### **36V** Brushless 40mm SDS-MAX **Rotary Hammer Kit** \_\_\_\_

00

DH3640DA(GAZ)

- Hammer Drilling or Chiseling modes
- Huge 9.2J impact energy
- User Vibration Protection (UVP)
- 4-stage speed selector
- Variable and constant speed control

Supplied with 2x1440W Multi Volt Batteries, Rapid Charger, Case.



HíKOKI

Impact Energy	9.2J
Bit Size	SDS-MAX
User Vibration Protection	UVP + LVH
Masonry	40mm
No Load Speed	0 - 500/min
Full Impact Rate	0 - 2,800/min
Weight	7.4kg (BSL36B18X)
Voltage	36V



#### 1.150W AC Brushless 40mm **SDS-MAX Rotary Hammer**

DH40MEY2(G1Z)

- Hammer Drilling or Chiseling modes
- Huge 9.2J impact energy
- User Vibration Protection (UVP)
- 4-stage speed selector
- Variable and constant speed control

Supplied with Side Handle, Grease, Case.

Impact Energy	9.23
Bit Size	SDS-MAX
Wattage	1,150W
Masonry	40mm
No Load Speed	250 - 500/min
Full Impact Rate	0 - 2,800/min
Weight	6.8kg
Voltage	230V

#### 1.340W 45J AC **Demolition Hammer**

H65SB3(G1Z)

- 45J of impact energy
- Demolish 338kg of concrete in 30mins
- Heavy Duty Alloy Hybrid Body (AHB)
- User Vibration Protection (UVP)
- Auto-stop brushes for added motor protection

Supplied with bull point, carry case with castors

Impact Energy	453
Bit Size	30mm Hex.
Wattage	1,340W
Anti-Vibration System	UVP
Full Impact Rate	1,600/min
Overall Length	731mm
Weight	18kg
Voltage	230V



n y Gi Scan for tool specs.

Scan for tool specs

#### 36V Brushless 28mm SDS+ **Rotary Hammer Kit** DH3628DC(GGZ)

■ Rotary Drilling, Hammer Drilling,

- Chiseling modes
- LED Level and Autostop
- 99.7% HEPA dust extraction

■ LVH, RFC and UVP protection

Supplied with 2x 1080W Multi Volt Batteries,

Rapid Charger, Dust Extractor, Quick release chuck

Impact Energy	3.2J
Bit Size	SDS+
User Vibration Protection	UVP + LVH
Masonry	28mm
No Load Speed	0 - 950/min
Full Impact Rate	0 - 4,300/min
Weight	5.2kg (BSL36A18X)
Voltage	36V



230

HIKOK

#### 1,250W 22J AC SDS-MAX **Demolition Hammer** H60MC(G1Z)

- Powerful, compact and robust model
- SDS-MAX variable lock mechanism
- 12 step tool adjustment angle
- Huge demolition capacity of 22J
- Quick release bit holder

Supplied with side handle, case, bull point.

Impact Energy	22J
Bit Size	SDS-MAX
Wattage	1,250W
Adjustment Angle	12 steps
Full Impact Rate	1,600/min
Overall Length	570mm
Weight	10.2kg
Voltage	230V



Scan for tool specs.

#### 2,000W 70J AC Demolition Hammer H90SG(G1Z)

- 70J of impact energy
- Demolish 512kg of concrete in 30mins
- Heavy Duty Alloy Hybrid Body (AHB)
- User Vibration Protection (UVP)
- Optimised hammer mechanism

Supplied with Hex. Bar Wrench

Impact Energy	70J
Bit Size	28.5mm Hex.
Wattage	2,000W
Anti-Vibration System	UVP
Full Impact Rate	1,000/min
Overall Length	860mm
Weight	32kg
Voltage	230V





Scan for tool specs.







#### **REDEEM A BONUS 2160W MULTI VOLT TFPWR BATTERY** WORTH \$369 WHEN YOU BUY A QUALIFYING 3+ TOOL COMBO KIT



KC363DRBL(GRZ)

KC363DC(GRZ)







KC183610DE(GRZ)



TERMS & CONDITIONS APPLY.

Offer valid for purchases from 1 August – 30 November 2024.

Redemption closes on 15th December 2024. Not in conjunction with any other bonus offer. While stocks last. Bonus is a BSL3640MVT. Bonus value is based on MSRP. Redemption items will be dispatched within 6 weeks of receipt claim. Proof of purchase and photo of barcode required. For terms & conditions, list of qualifying kits and to redeem, go to www.hikoki.co.nz/promotions/

SCAN TO REDEEM



REDEEM

HÍKOKI TFPWR

REDEEM A BONUS 2160W MULTI VOLT T/PWR BATTERY WORTH \$369 WHEN YOU BUY 2x QUALIFYING 36V BARE TOOLS

# Hikoki TPWR

Terms & Conditions Apply. Offer valid for purchases from 1 August – 30 November 2024. Redemption closes on 15th December 2024. Not in conjunction with any other bonus offer. Bonus is a BSL3640MVT. While stocks last. Purchases must be transacted on one receipt to qualify. Proof of purchase and photo of barcode required. Bonus value is based on MSRP. For terms & conditions, list of qualifying 36V Bare Tools and to redeem, go to www.hikoki.co.nz/promotions/



36V

SCAN TO REDEEM



#### REDEEM A BOBDUS BODDUS BODDUS

F

I

### WHEN YOU BUY AN AC 255mm WORKSITE TABLE SAW

HIKOKI 18V E





Terms & Conditions Apply. Offer valid for purchases from 1 August - 30 November 2024. Only while promotional stocks last. Qualifying tool is C10RJ. The bonus is an 18V Brushless Air Duster + 18V Li-ion Battery + Charger (PROMORA18DAKIT). Redemption closes on 15th December 2024. Not in conjunction with any other bonus offer. Strictly while promotional stocks last. Proof of purchase and photo of barcode required to validate the claim. Allow up to 6 weeks for bonus to be dispatched. For full details and to redeem, go to www.hikoki.co.nz/promotion/